

## Liebert XD0 Overhead Cooling Module

*Sensible Spot And Zone Cooling For High Heat Density Equipment*



**The ceiling mounted Liebert XD0 overhead cooling module provides sensible spot and zone cooling for high heat density equipment.**

The Liebert XD0 draws in hot air through two opposite inlets and discharges cool air down into the cold aisle where the electronic equipment air inlets are located. This flexible, scalable and space saving product mounts to the ceiling — requiring zero floor space.

The Liebert XD0 is a part of our high heat-density cooling product family that utilizes pumped refrigerant technology. The pumped refrigerant operates at low pressure in the system and becomes a gas at room conditions, making it ideal for use around electronic equipment. Since the Liebert XD0 always provides 100% sensible capacity, the need for humidification is significantly reduced, further reducing energy usage and maintenance.

### Key Features


- Can cool more than 500 W/sq.ft. (5400 W/m<sup>2</sup>).
- No floor space required.
- Complements the cooling of Liebert precision cooling units.
- Superior cost for cooling per high heat density rack.
- Excellent for spot and zone cooling.
- Uses pumped refrigerant, which is ideal for use around electronic equipment.
- Highly Energy Efficient.
- Scalable.
- Flexible installation with several connection possibilities.
- Optional pre-charged flexible piping with threaded quick-connect fittings allows adaptive and scalable expansion without interruption of cooling operations.
- Possible to be fully installed from an existing cold aisle without the need for reaching over existing racks.
- Complete packaged unit includes enclosure, coils, fan and piping.

## Technical Data


Nominal Capacity, 60 Hz <sup>1</sup>	20 kW / 5.7 Ton
Nominal Capacity, 50 Hz <sup>1</sup>	17.7 kW / 5 Ton
Nominal Airflow, 60Hz	2700 CFM (4590 m <sup>3</sup> /h)
Nominal Airflow, 50Hz	2250 CFM (3820 m <sup>3</sup> /h)
Input Voltage	120 V, 1 ph, 60 Hz 230 V, 1 ph, 50/60 Hz
Full load amps	2.7A @ 120V, 1ph, 60 Hz 1.5A @ 230V, 1ph, 50 Hz
Height	22.5" (572 mm)
Width	72.0" (1829 mm)
Depth	24" (610 mm)
Weight	150 lbs (68 kg)
Options	Condensate Detection (dry contacts) Quick Connect Couplings (for Flexible Piping)

<sup>1</sup>Nominal Capacity Rating @ 55 °F (13 °C) Entering Fluid Temperature and 98 °F (37 °C) Entering Air Temperature.  
Max capacity @ 55 °F (13 °C) EFT is 23.5 kW @ 100 °F (37.8 °C) EAT for 60 Hz and 23.5 kW @ 104 °F (40 °C) EAT for 50 Hz.

## Liebert XD Hydraulic System Schematic




The indoor Liebert XDC refrigerant chiller is specifically designed to support Liebert XD cooling modules. The Liebert XDC connects directly to the XD modules.



When a building chilled water system is available, the Liebert XDP pumping unit is utilized as an interface between the pumped refrigerant circuit and the chilled water system.

Both the Liebert XDC and the XDP units circulate the refrigerant to Liebert XD units, while maintaining the refrigerant at a temperature always above the actual dewpoint.



The Liebert XDO systems work extremely well with the "hot aisle-cold aisle" approach.

## Liebert Corporation

1050 Dearborn Drive  
P.O. Box 29186  
Columbus, Ohio 43229  
800 877 9222 Phone (U.S. & Canada Only)  
614 888 0246 Phone (Outside U.S.)  
614 841 6022 FAX

Via Leonardo Da Vinci 8  
Zona Industriale Tognana  
35028 Piove Di Sacco (PD)  
Italy  
39 049 9719 111 Phone  
39 049 5841 257 FAX

Emerson Network Power Asia Pacific  
7/F., Dah Sing Financial Centre  
108 Gloucester Rd, Wanchai  
Hong Kong  
852 2572201 Phone  
852 28029250 FAX

## liebert.com

### 24 x 7 Tech Support

800 222 5877 Phone  
614 841 6755 (outside U.S.)

While every precaution has been taken to ensure accuracy and completeness in this literature, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

© 2006 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice.

All names referred to are trademarks or registered trademarks of their respective owners.

© Liebert and the Liebert logo are registered trademarks of the Liebert Corporation.

SL-16665 (09/06) Printed in USA

## Emerson Network Power.

The global leader in enabling Business-Critical Continuity™.

- AC Power Systems
- Connectivity
- DC Power Systems
- Embedded Computing
- Embedded Power
- Integrated Cabinet Solutions
- Outside Plant
- Power Switching & Control
- Precision Cooling**
- Services
- Site Monitoring
- Surge Protection

## Emerson Network Power.com

Business-Critical Continuity, Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co. ©2006 Emerson Electric Co.